


INDUSTRIAL COMPONENT DATA

DIKD 1,5-TG 2774237 PHOENIX CONTACT Sensor/actuator terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DIKD 1,5-TG



Manufacturer	PHOENIX CONTACT
MPN / Reference	DIKD 1,5-TG
Catalog number	2774237
Category	Sensor/actuator terminal block
Minimum order	50 Pcs
Document ID	EO-B5B844A44D
Generated	2026-08-02

Product Overview

Sensor/actuator terminal block

Terminal for detectors/actuators, The current and voltage are determined by the connector used., nominal voltage: 250 V, nominal current: 15 A, 1., 2. and 3rd floor, connection type: Screw connection, Dimensioning section: 2.5 mm², section: 0.2 mm² - 4 mm², connection type: Screw connection, Dimensioning section: 2.5 mm², section: 0.2 mm² - 4 mm², Mounting: NS 35/7.5, NS 35/15, color: gray

Terminal block for sensors/actuators, Amperage and voltage depend on the plug used., Nominal voltage: 250 V, Nominal current: 15 A, 1., 2. and 3. Floor, connection type: Screwed connection, Reference section: 2.5 mm², cross-section: 0.2 mm² - 4 mm², connection type: Screwed connection, Reference section: 2.5 mm², Cross-section: 0.2 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 2774237

Packing unit 50 pc

Catalog page Page 445 (C-1-2017)

GTIN 4017918126773

Weight per Piece (excluding packing) 20.150 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 3

Number of connections 6

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 15 A

Maximum load current 15 A (with 4 mm² conductor cross section)

Nominal voltage U_N 250 V (the voltage is determined by the component used)

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N(upper level) 15 A

Maximum load current (upper level) 15 A (with 4 mm² conductor cross section)

Nominal voltage U_N 250 V

Open side panel No

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Checking the mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DIKD 1,5-TG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.