

## INDUSTRIAL COMPONENT DATA

# SF-7EP1N8AAK00 1607047 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: SF-7EP1N8AAK00



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | SF-7EP1N8AAK00                    |
| Catalog number  | 1607047                           |
| Category        | Sensor-actuator connector chassis |
| Minimum order   | 16 Pcs                            |
| Document ID     | EO-061929D09E                     |
| Generated       | 2026-08-04                        |

## Product Overview

Device connector, front mounting

Conect. plug. to be apar. front wall, Fixed angle, increased flange size, Screw lock, M23, number of poles: 4+3+PE, contact type: Male, Axial O-ring, 4x Ø 3.2, shielded: yes, flange size: 28 mm x 28 mm, protection index: IP67, cable diameter range: 0 mm ... 0 mm, number of poles: 8, connection type: Crimped connection, series: SF

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |
|--------------|-------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1607047

Packing unit 16 pc

Note Made to Order (non-returnable)

GTIN 4046356253741

Weight per Piece (excluding packing) 123.560 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts 4 x Ø 1 mm, 4 x Ø 2 mm separately

Type of locking Screw locking

Coding N

Contact connection method Crimp connection  
Type of contacts Pin  
Number of positions 8  
Contact diameter of power contacts 2 mm  
Nominal current per power contact at 25°C 30 A  
Contact diameter of signal contacts 1 mm  
Nominal current per signal contact at 25°C 9 A  
Conductor entry 0 mm ... 0 mm  
Pg housing screw connection none  
Mounting type 4x Ø 3.2  
Ambient conditions  
Ambient temperature -40 °C ... 125 °C  
Degree of protection IP67  
Material  
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)  
Insulator material PA 6.6  
Gasket and O-ring material FPM  
Specifications according to DIN EN 61984:2001  
Installation height max. 3000 m  
Nominal / operating voltage of power contacts 630 V  
Rated surge voltage of power contacts 6 kV  
Overvoltage category of power contacts III  
Degree of pollution of power contacts 3  
Nominal / operating voltage of signal contacts 250 V  
Rated surge voltage of signal contacts 4 kV  
Overvoltage category of signal contacts III  
Degree of pollution of signal contacts 3  
Environmental Product Compliance  
China RoHS Environmentally Friendly Use Period = 50  
For details about hazardous substances go to tab....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SF-7EP1N8AAK00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.