

INDUSTRIAL COMPONENT DATA

SF-7EP1N8ACLB2 1607053 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SF-7EP1N8ACLB2



Manufacturer	PHOENIX CONTACT
MPN / Reference	SF-7EP1N8ACLB2
Catalog number	1607053
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-BEB83DC17B
Generated	2026-08-06

Product Overview

Rear panel feed-through

Rear wall pass-through, long straight, Screw lock, M23, number of poles: 4+3+PE, contact type: Male, Axial O-ring, 4xM3, shielded: yes, protection index: IP67, cable diameter range: 12 mm ... 15 mm, number of poles: 8, connection type: Crimped connection, series: SF, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242229
 Bushing Rear Side, Straight, Long, Screw Lock, M23, Number of Poles: 4+3+PE, Contact Type: Male, Axial O-Ring, 4xM3, Shielded: Yes, Cable Diameter Range: 12 mm ... 15 mm, Number of poles: 8, Connection type: Crimp connection, series: SF, Replacement product according to RoHS II without exception 6c (Pb < 0.1%) Reference: 1242229

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1607053

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 156 (C-2-2017)

GTIN 4046356253802

Weight per Piece (excluding packing) 130.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts 4 x Ø 1 mm, 4 x Ø 2 mm separately

Type of locking Screw locking

Coding N

Contact connection method Crimp connection

Type of contacts Pin

Number of positions 8

Contact diameter of power contacts 2 mm

Nominal current per power contact at 25°C 30 A

Contact diameter of signal contacts 1 mm

Nominal current per signal contact at 25°C 9 A

Conductor entry 12 mm ... 15 mm

Pg housing screw connection none

Mounting type 4x M3

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Material

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Insulator material PA 6.6

Gasket and O-ring material FPM

Specifications according to DIN EN 61984:2001

Installation height max. 3000 m

Nominal / operating voltage of power contacts 630 V

Rated surge voltage of power contacts 6 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Nominal / operating voltage of signal contacts 630 V

Overvoltage category of signal contacts III

Degree of pollution of signal contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substanc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SF-7EP1N8ACLB2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.