

INDUSTRIAL COMPONENT DATA

SHK-0478/05,00 1627074 PHOENIX CONTACT Assembled cable connectors SHK-0478/05,00 1627074

Brand: PHOENIX CONTACT | Manufacturer Part Number: SHK-0478/05,00



Manufacturer	PHOENIX CONTACT
MPN / Reference	SHK-0478/05,00
Catalog number	1627074
Category	Circular connector, mounting (without cable)
Minimum order	10 Pcs
Document ID	EO-61402B9E00
Generated	2026-08-04

Product Overview

Assembled cable connectors - SHK-0478/05,00 - 1627074

Ready-made industrial connectors, length: 5 m, outer wrap colour: orange RAL 2003

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Assembled cable connectors, length: 5 m, color of outer sheath: orange RAL 2003

Key Commercial Data

Orderkey 1627074

Packing unit 1

GTIN 4055626310664

Custom tariff number 85444290

Conductor length 5 m

Connector specifications

Type gerade, konfektioniert

Thread type M23

Locking type SPEEDCON locking

Degree of protection IP67, when in locked state

Number of positions 4+4+PE

Direction of rotation Standard

Type of contact Pin
Max. current 30 A
Voltage 630 V AC
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Cable specifications
Shielded yes
Cable structure (4 x 4 + (2 x 1.0))
External cable diameter ± 14.6 mm 0.6 mm
Outer sheath, material PUR
Material wire insulation PP (halogen-free)
External sheath, color orange RAL 2003
Single wire, color Black 1, black 2, black 3, green-yellow Power wires + PE
white, brown Signal wires
Nominal voltage, cable 1000 V
Test voltage 4 kV
Smallest bending radius, fixed installation 58 mm
Smallest bending radius, movable installation 109 mm
Acceleration 10 m/s²
Ambient temperature for fixed installation -40 °C ... 80 °C
Ambient temperature for flexible installation -30 °C ... 60 °C
Special properties Flexible cable conduit capable
Flame resistance IEC 60332-1-2
Halogen-free yes, PUR sheath
Resistance to oil yes, PUR sheath
Environmental Product Compliance
REACH SVHC
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declar..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SHK-0478/05,00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.