

INDUSTRIAL COMPONENT DATA

EMPPR (27X15) 0829535 PHOENIX CONTACT Shock protection

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMPPR (27X15)



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMPPR (27X15)
Catalog number	0829535
Category	Drawing cover
Minimum order	50 Pcs
Document ID	EO-D1CB03EC34
Generated	2026-08-03

Product Overview

Shock protection

Protection against accidental contacts, Elbow, transparent, unlabeled, mounting class: interlock, useful surface: 27 x 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0829535

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 351 (C-3-2017)

GTIN 4046356614931

Weight per Piece (excluding packing) 0.100 g

Custom tariff number 39204910

Country of origin DE (Germany)

Dimensions

Length (b) 15 mm

Width (a) 27 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 70 °C

Recommended storage conditions 10-30 °C / 40-70 % relative humidity. Storage in a cool and dry place is recommended.

General

Color transparent

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO₂ test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Foil strength 300 µm

Marking mounting type snapped into marker carrier

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flammability rating according to UL 94 V0

Classifications

eCl@ss 10.0.127400629eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127141100eCl@ss
6.027149100eCl@ss 7.027149129eCl@ss 8.027149129eCl@ss

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMPPR (27X15) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.