

INDUSTRIAL COMPONENT DATA

WMS 19,1 (60X30)R CUS 0800742 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 19,1 (60X30)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 19,1 (60X30)R CUS
Catalog number	0800742
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-9843F73BA6
Generated	2026-08-01

Product Overview

Shrink sleeve

Heat shrink tubing, Roll, white: custom, Perforated, mounting class: sliding, cable diameter range: 6.4 ... 19.1 mm, usable surface: 60 x 30 mm

Shrink sleeve, Roll, white: user-defined, perforated, mounting type: slide-on, cable diameter range: 6.4 ... 19.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Shrink sleeve printed

Type Shrink sleeve

Data management status

Article revision 01

Marking

Number of individual labels per row 1

Printing user-defined

Identification technology Thermal transfer for rolls

DimensionsWidth 30 mm

Length 60 mm

External dimensions

Outside diameter 6.4 mm ... 19.1 mm

Material specificationsRoHS compliant yes

Color white (RAL 9010)

Material Polyolefine

Base element material polyolefine

Shrink rate 3:1

Components halogen-free

Shrink temperature > 85 °C

Cable/lineExternal cable diameter 6.4 mm ... 19.1 mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements ≥ 5 N

Result Test passed

Tesafilm test

Specification DIN EN ISO 2409:2013 (following)

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h

Temperature resistance

Specification ANSI/UL 969-2018:03 (following)

Test duration 240 h

Rating 125 °C (150 °C) Test passed

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-01):2020-03

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Isopropyl

[CAS No. 67-63-0] Test passed

n-Hexane

[CAS No. 110-54-3] Test passed

Water + Petroleum ether

[CAS No. 64742-82-1] Test passed

Sodium hydroxide 0.1 mol/l

[CAS No. 1310-73-2] Test passed

Ethanol (99 %)

[CAS No.....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 19,1 (60X30)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.