


INDUSTRIAL COMPONENT DATA

WMS 2,4 (15X4)RXL 0800396 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 2,4 (15X4)RXL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 2,4 (15X4)RXL
Catalog number	0800396
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-9811CF4E65
Generated	2026-08-02

Product Overview

Shrink sleeve

Heat-shrink tubing, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, Perforated, mounting class: slip, cable diameter range: 0.8 ... 2.4 mm, usable area: 15x4mm, Number of individual indexes: 10000

Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, perforated, mounting type: slide-on, cable diameter range: 0.8 ... 2.4 mm, Number of individual labels: 10000, text field height: 4 mm, text field width: 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesNote on application For the THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK ROLLMASTER 300/600, and THERMOMARK E.300 (D)/E.600 (D) roll printers, this material can only be processed outside of the printer using the integrated material dispenser pack.

Material information The specified minimum wire diameter of the shrink sleeve refers to its use as a marking material and does not guarantee any insulation characteristics once shrunk.

Depending on the processed material batch, as well as the storage and processing conditions, the maximum insertable wire diameter may be reduced.

Product propertiesProduct type Shrink sleeve

Type Shrink sleeve

Data management status

Article revision 05

Marking

Number of individual labels 10000

Number of individual labels per row 4

Identification technology Thermal transfer for rolls

DimensionsWidth 4 mm

Text field width 15.00 mm

Text field height 4.00 mm

Length 15 mm

External dimensions

Outside diameter 0.8 mm ... 2.4 mm

Material specificationsRoHS compliant yes

Color white (RAL 9010)

Material Polyolefine

Base element material polyolefine

Shrink rate 3:1

Components halogen-free

Shrink temperature > 85 °C

Cable/lineExternal cable diameter 0.8 mm ... 2.4 mm

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (following)

Requirements >= 5 N

Result Test passed

Tesafilm t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 2,4 (15X4)RXL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.