

INDUSTRIAL COMPONENT DATA

WMS 25,4 (EX40)R CUS 0800709 PHOENIX CONTACT Shrink sleeve, Roll, white, labeled according to customer speci..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 25,4 (EX40)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 25,4 (EX40)R CUS
Catalog number	0800709
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-51DF3746F9
Generated	2026-07-29

Product Overview

Shrink sleeve, Roll, white, labeled according to customer specifications, Perforated, Mounting type: slide on, Cable diameter: 8.5-25.4 mm

Heat Shrink Casing, Roll, White: Customized, Drilled or Cut, Mounting Class: Slip, Cable Diameter Range: 8.5 ... 25.4 mm, usable area: max. 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Dimensions

Width (a) 40 mm

Cable diameter 8.5 mm ... 25.4 mm

Ambient conditions

Ambient temperature (operation) -55 °C ... 135 °C

General

Color white

Base element material polyolefine

Components Halogen-free

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 25,4 (EX40)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.