

INDUSTRIAL COMPONENT DATA

WMS 25,4 (EX40)RL YE 0800335 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 25,4 (EX40)RL YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 25,4 (EX40)RL YE
Catalog number	0800335
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-AA8686E362
Generated	2026-07-29

Product Overview

Shrink sleeve

Heat shrink tubing, Roll, yellow, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2: unprinted, unperforated, mounting class: slip, cable diameter range: 8.5 ... 25.4 mm, usable area: 40x60000mm, length. Roll: 60 m

Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMASTER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, unperforated, mounting type: slide-on, cable diameter range: 8.5 ... 25.4 mm, Number of individual labels: 1, roll length: 60 m, text field height: 40 mm, text field width: 60000 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesNote on application For the THERMOMARK ROLL and THERMOMARK ROLL 2.0 roll printers, this material can only be processed with an external media hub.

Material information The specified minimum wire diameter of the shrink sleeve refers to its use as a marking material and does not guarantee any insulation characteristics once shrunk.

Depending on the processed material batch, as well as the storage and processing conditions, the maximum insertable wire diameter may be reduced.

Product propertiesProduct type Shrink sleeve

Type Shrink sleeve
Data management status
Article revision 03
Marking
Number of individual labels 1
Identification technology Thermal transfer for rolls
Dimensions Width 40 mm
Text field width 60000.00 mm
Text field height 40.00 mm
Length of roll 60.00 m
External dimensions
Outside diameter 8.5 mm ... 25.4 mm
Material specifications RoHS compliant yes
Color yellow (RAL 1018)
Material Polyolefine
Base element material polyolefine
Shrink rate 3:1
Components halogen-free
Shrink temperature > 85 °C
Cable/line External cable diameter 8.5 mm ... 25.4 mm
Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 25,4 (EX40)RL YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.