

**INDUSTRIAL COMPONENT DATA**

# WMS 3,2 (30X5)R CUS 0800746 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 3,2 (30X5)R CUS



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | WMS 3,2 (30X5)R CUS |
| Catalog number  | 0800746             |
| Category        | Cable coding system |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-1F087AFA42       |
| Generated       | 2026-08-03          |

## Product Overview

Shrink sleeve

Heat Shrink Tubing, Roll, White: Customized, Perforated, Mounting Class: Slip, Cable Diameter Range: 1 ... 3.2 mm, usable area: 30x5mm

Heat shrink sleeve, Roll, white: customized, Perforated, mounting class: slip, cable diameter range: 1 ... 3.2 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 0800746

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 202 (C-5-2013)

GTIN 4046356628808

Weight per Piece (excluding packing) 0.600 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 30 mm

Width (a) 5 mm

Cable diameter 1 mm ... 3.2 mm

Ambient conditions

Ambient temperature (operation) -55 °C ... 135 °C

General

Color white

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing user-defined

Number of individual labels per row 2

Marking mounting type slide on

Standards and Regulations

Connection in acc. with standard CSA

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Classifications

eCl@ss 4.0 24190219 eCl@ss 4.1 24190219 eCl@ss 5.0 27400401 eCl@ss 5.1 27400100 eCl@ss 6.0 27400100 eCl@ss 7.0 27400105 eCl@ss 8.0 27400105 eCl@ss 9.0 27400401

ETIM 2.0 EC000761 ETIM 3.0 EC001530 ETIM 4.0 EC001530 ETIM 5.0 EC000217 ETIM 6.0 EC001530

UNSPSC 6.01 30211811 UNSPSC 7.0901 39121410 UNSPSC 11 39121410 UNSPSC 12.01 39121410 UNSPSC 13.2 39131504

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 3,2 (30X5)R CUS with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.