

INDUSTRIAL COMPONENT DATA

WMS 4,8 (60X9)R CUS 0800738 PHOENIX CONTACT Shrink sleeve, Roll, white, labeled according to customer specif..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 4,8 (60X9)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 4,8 (60X9)R CUS
Catalog number	0800738
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-7F5B343904
Generated	2026-07-29

Product Overview

Shrink sleeve, Roll, white, labeled according to customer specifications, Perforated, Mounting type: slide on, Cable diameter: 1.6-4.8 mm

Heat Shrink Tubing, Roll, White: Customized, Perforated, Mounting Class: Slip, Cable Diameter Range: 1.6 ... 4.8 mm, usable area: 60 x 9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Dimensions

Length (b) 60 mm

Width (a) 9 mm

Cable diameter 1.6 mm ... 4.8 mm

Ambient conditions

Ambient temperature (operation) -55 °C ... 135 °C

General

Color white

Base element material polyolefine

Components Halogen-free

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels per row 1

Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 4,8 (60X9)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.