

INDUSTRIAL COMPONENT DATA

WMS 6,4 (60X10)R YE CUS 0800758 PHOENIX CONTACT

Shrink sleeve, Roll, yellow, labeled according to customer s..

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS 6,4 (60X10)R YE CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS 6,4 (60X10)R YE CUS
Catalog number	0800758
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-1687190DBA
Generated	2026-08-03

Product Overview

Shrink sleeve, Roll, yellow, labeled according to customer specifications, Perforated, Mounting type: slide on, Cable diameter: 2.1-6.4 mm, Lettering field: 60 x 10 mm

Heat shrink tubing, Roll, yellow: custom, Perforated, mounting class: sliding, cable diameter range: 2.1 ... 6.4 mm, usable surface: 60 x 10 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Dimensions

Length (b) 60 mm

Width (a) 10 mm

Cable diameter 2.1 mm ... 6.4 mm

Ambient conditions

Ambient temperature (operation) -55 °C ... 135 °C

General

Color yellow

Base element material polyolefine

Components Halogen-free

Material Polyolefine

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels per row 1

Marking mounting type slide on

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS 6,4 (60X10)R YE CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.