

INDUSTRIAL COMPONENT DATA

WMS-2 HF 2,4 (60X4)RL 0801008 PHOENIX CONTACT Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 2,4 (60X4)RL



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 2,4 (60X4)RL
Catalog number	0801008
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-17A74817E9
Generated	2026-08-05

Product Overview

Shrink sleeve

Heat shrink tubing, roller, white, unlabeled, 2:1 shrinkage rate, labelable with: THERMOMARK ROLL, THERMOMARK X.1, perforated, mounting type: insertion

Shrink sleeve, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLLMARKER 300/600, THERMOMARK ROLL X1, THERMOMARK ROLL, THERMOMARK ROLL 2.0, THERMOMARK W, THERMOMARK X1.2, unperforated, mounting type: slide-on, cable diameter range: 1.2 ... 2.4 mm, Number of individual labels: 1000, text field height: 4 mm, text field width: 60 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material
--------------	-------------------------------

Additional Product Information

Technical dataNotesMaterial information The specified minimum wire diameter of the shrink sleeve refers to its use as a marking material and does not guarantee any insulation characteristics once shrunk.

Depending on the processed material batch, as well as the storage and processing conditions, the maximum insertable wire diameter may be reduced.

Product propertiesProduct type Shrink sleeve

Area of application Railway industry

Type Shrink sleeve

Data management status

Article revision 00

Marking

Number of individual labels 1000

Number of individual labels per row 1

Identification technology Thermal transfer for rolls

Dimensions Width 4 mm

Text field width 60.00 mm

Text field height 4.00 mm

Length 60 mm

External dimensions

Outside diameter 1.2 mm ... 2.4 mm

Material specifications Color white (RAL 9010)

Material Polyolefine

Base element material polyolefine

Shrink rate 2:1

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Components halogen-free

Shrink temperature > 90 °C

Cable/line External cable diameter 1.2 mm ... 2.4 mm

Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish

Result Test passed

Test for substances that would hinder coating with paint or varnish

Result Test passed

Scratch test for the determining scratch resistance

Specification DIN EN ISO 1518-1:2019-10 (follow...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 2,4 (60X4)RL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.