


INDUSTRIAL COMPONENT DATA

WMS-2 HF 2,4 (15X4)RL YE 0801004 PHOENIX CONTACT

Shrink sleeve

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMS-2 HF 2,4 (15X4)RL YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMS-2 HF 2,4 (15X4)RL YE
Catalog number	0801004
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-E30DDF2248
Generated	2026-08-06

Product Overview

Shrink sleeve

Heat shrink tubing, roller, yellow, unlabeled, 2:1 shrinkage rate, labelable with: THERMOMARK ROLL, THERMOMARK X.1, perforated, mounting type: insertion

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > MS Material**

Additional Product Information

Key Commercial Data

Orderkey 0801004

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 228 (C-3-2017)

GTIN 4055626043944

Weight per Piece (excluding packing) 614.400 g

Custom tariff number 39173200

Country of origin DK (Denmark)

Dimensions

Length (b) 15 mm

Width (a) 4 mm

Cable diameter 1.2 mm ... 2.4 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 105 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color yellow

Base element material polyolefine

Type Shrink sleeve

Components halogen-free

Material Polyolefine

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Printing without print

Number of individual labels 4000

Number of individual labels per row 4

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146723 THERMOMARK ROLL X1

5146231 THERMOMARK X1.2

5146147 THERMOMARK W2

0804501 THERMOMARK ROLLMASTER 300

Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF

0801358 THERMOMARK-RIBBON 110-WMSU

0801360 THERMOMARK-RIBBON 64-WMSU

0803390 THERMOMARK-RIBBON 25-WMSU

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of tes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMS-2 HF 2,4 (15X4)RL YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.