

INDUSTRIAL COMPONENT DATA

PLC-PT-EIK 1-SVN 24P/P 2900397 PHOENIX CONTACT

Solid-state relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLC-PT-EIK 1-SVN 24P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLC-PT-EIK 1-SVN 24P/P
Catalog number	2900397
Category	Optocoupler
Minimum order	1 Pcs
Document ID	EO-56D0AB7309
Generated	2026-08-01

Product Overview

Solid-state relay module

PLC-INTERFACE for NAMUR applications, consisting of PLC-BPT.../21 base terminal block with push-in connection and integrated circuit, for installation on DIN rail NS 35/7.5, output with positive switching, supply voltage 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2900397

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 420 (C-5-2017)

GTIN 4046356506779

Weight per Piece (excluding packing) 31.130 g

Custom tariff number 85369010

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 6.2 mm

Height 80 mm
Depth 86 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 50 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Degree of protection IP20
Input data
Designation Device supply
Nominal input voltage UN 24 V DC $\pm 20\%$
Input voltage range in reference to UN 0.8 ... 1.2
Input voltage range 19.2 V DC ... 26.4 V DC
Typical input current at UN approx. 14 mA
Max. current consumption approx. 70 mA (at 50 mA output current)
Operating voltage display Green LED
Type of protection Reverse polarity protection
Surge protection
Protective circuit/component Polarity protection diode
Suppressor diode
Designation Control circuit
Nominal input voltage UN 8.2 V DC $\pm 10\%$
Type of protection Surge protection
Protective circuit/component Suppressor diode
Non-load voltage 8.2 V DC $\pm 10\%$
Switching point ≥ 2.1 mA (In conductive state)
 ≤ 1.2 mA (In blocking state)
6.3 mA ... 10 mA (in the event of a short-circuit)
0 mA ... 0.35 mA (In the event of a wire break)
Switching hysteresis approx. 0.2 mA
Internal resistance approx. 1 k Ω
Cable length < 30 m
Power dissipation for nominal condition 0.34 W
Ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLC-PT-EIK 1-SVN 24P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.