

INDUSTRIAL COMPONENT DATA

PSR-SPP- 24UC/URM4/5X1/2X2/B 2981046 PHOENIX CONTACT Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SPP-24UC/URM4/5X1/2X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SPP-24UC/URM4/5X1/2X2/B
Catalog number	2981046
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-9A458EF8EF
Generated	2026-08-01

Product Overview

Extension module

Single- or dual-channel contact extension, 5 NO contacts, 1 NC contact, 1 feedback circuit, width: 22.5 mm, plug-in push-in terminal block

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2981046

Packing unit 1 pc

Catalog page Page 263 (C-6-2017)

GTIN 4017918915520

Weight per Piece (excluding packing) 20.400 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 22.5 mm

Height 112 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C (observe derating)

Ambient temperature (storage/transport) -40 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude max. 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US 24 V AC/DC -15 % / +10 %

Rated control supply current IS typ. 81 mA AC

typ. 71 mA DC

Power consumption at US typ. 1.94 W (AC)

typ. 1.7 W (DC)

Inrush current 175 mA ($t = 5$ ms at U_s)

Typ. starting time with $U_s < 20$ ms (when controlled via A1)

Typical release time < 20 ms (when controlled via A1)

Recovery time < 1 s

Operating voltage display 1 x green LED

Protective circuit Surge protection Varistor

Maximum switching frequency 1 Hz

Filter time 2 ms (at A1 in the event of voltage dips at U_s)

Output data

Contact type 5 enabling current paths

1 confirmation current path

1 signaling current path

Contact material AgSnO₂

Maximum switching voltage 250 V AC/DC (Observe the load curve)

Minim...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SPP-24UC/URM4/5X1/2X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.