

INDUSTRIAL COMPONENT DATA

PSR-SCP-24DC/URML4/3X1/1X2/B 2903583 PHOENIX CONTACT Extension module

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSR-SCP-24DC/URML4/3X1/1X2/B



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSR-SCP-24DC/URML4/3X1/1X2/B
Catalog number	2903583
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-206863A59C
Generated	2026-08-06

Product Overview

Extension module

Extension of single- or two-channel contacts for OSSD signals (e.g. light curtain), 3 NO contacts, 1 NC contact, up to category 4, PL e according to EN ISO 13849, SIL 3 according to EN 62061, plug-in screw terminals, width: 22.5 mm

Single or two-channel contact extension for OSSD signals (e.g. light curtain), 3 NO contacts, 1 NC, up to Cat. 4 PL e according to EN ISO 13849, SIL 3 according to EN IEC 62061, pluggable screw terminals, width 22.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2903583

Packing unit 1 pc

Catalog page Page 263 (C-6-2017)

GTIN 4046356751698

Weight per Piece (excluding packing) 210.900 g

Custom tariff number 85371098

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 22.5 mm

Height 99 mm

Depth 114.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Ambient temperature (storage/transport) -40 °C ... 70 °C

Max. permissible relative humidity (operation) 75 % (on average, 85% infrequently, non-condensing)

Max. permissible humidity (storage/transport) 75 % (on average, 85% infrequently, non-condensing)

Maximum altitude ≤ 2000 m (Above sea level)

Input data

Rated control circuit supply voltage US

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.85 ... 1.1

Typical input current at UN 70 mA DC

Voltage at input/start and feedback circuit 24 V DC

Typical response time 25 ms (man. start)

Typ. starting time with Us 100 ms (automatic start)

Typical release time 10 ms

Concurrence input 1/2 ?

Recovery time 1 s

Output data

Contact type 3 enabling current paths

1 signaling current path

Contact material AgSnO₂

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 15 V AC/DC

Limiting continuous current 6 A (N/C contact / N/O contact)

Maximum inrush current 6 A

Inrush current, minimum 25 mA

Sq. Total current 72 A₂(I_{TH2}= I₁₂+ I₂₂+ I₃₂)

Interrupting rating (ohmic load) max. 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSR-SCP-24DC/URML4/3X1/1X2/B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.