

INDUSTRIAL COMPONENT DATA

SK 3,8 REEL P3,5 WH CUS 0828495 PHOENIX CONTACT

Marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 3,8 REEL P3,5 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK 3,8 REEL P3,5 WH CUS
Catalog number	0828495
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-58A84335C9
Generated	2026-08-03

Product Overview

Marker strip

Strip card, available: per card, white, labelled according to customer specifications, mounting class: glued, for terminal width: 3.5 mm, usable surface: endless x 3.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0828495

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356512664

Weight per Piece (excluding packing) 0.500 g

Custom tariff number 49119900

Country of origin PL (Poland)

Dimensions

Width (a) 3.8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 15 °C

Recommended storage conditions 23 °C / 50% relative humidity. Storage in the original packaging is recommended prior to processing.

General

Note Marking up to max. 25-pos.

Color white

Type adhesive

Material Polyester

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of marker strips 12

Adhesive Acrylic

Printability Thermal transfer

Device 5146477 THERMOMARK ROLL

5146231 THERMOMARK X1.2

Ink ribbon 5145384 THERMOMARK-RIBBON 110

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 53 µm

Adhesive strength 20 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 3,8 REEL P3,5 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.