

## INDUSTRIAL COMPONENT DATA

**SK 7,5/3,8:FORTL.ZAHLEN 11-20 0804455:0011 PHOENIX CONTACT** Marker card, self-adhesive, labeled with the cons..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK 7,5/3,8:FORTL.ZAHLEN 11-20

PRODUCT IMAGE\nNOT  
AVAILABLE

|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | SK 7,5/3,8:FORTL.ZAHLEN 11-20 |
| Catalog number  | 0804455:0011                  |
| Category        | Labelling for terminal block  |
| Minimum order   | 10 Pcs                        |
| Document ID     | EO-60E5224E2B                 |
| Generated       | 2026-08-06                    |

**Product Overview**

Marker card, self-adhesive, labeled with the consecutive numbers: 11 ... 20, 10-section marker strips with 10 identical decades, white

Lettering card, self-adhesive, lettering with successive numbers: 11 ... 20, 10-piece lettering strip with 12 equal decades, white, for terminal width: 7.5 mm

Marker card, self-adhesive, labeled with the consecutive numbers: 11 ... 20, 10-section marker strips with 12 identical decades, white, for terminal block width: 7.5 mm, mounting type: adhesive

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path PHOENIX CONTACT &gt; MS Material

**Additional Product Information**

Technical dataProduct propertiesProduct type Labeled terminal marker

Pitch 7.5 mm

Type adhesive

Marking

Printing 11 ... 20

MountingMounting type adhesive

Material specificationsColor white (RAL 9010)

Material Polyester

Components free from silicone and halogen

Environmental and real-life conditionsUV resistance

Specification ISO 4892-2:2013-03 (following)

Wipe resistance of inscriptions

Specification DIN EN 61010-1 (VDE 0411-1):2011-07

DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Recommended ambient temperature (storage/transport) 23 °C

Recommended humidity (storage/transport) 50 %

DimensionsText field width 7.50 mm

Height 3.8 mm

Text field height 3.80 mm

Pitch 7.5 mm

Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK 7,5/3,8:FORTL.ZAHLEN 11-20 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.