

INDUSTRIAL COMPONENT DATA

SK U/2,8 P2,54 WH CUS 0825136 PHOENIX CONTACT Marker strip

Brand: PHOENIX CONTACT | Manufacturer Part Number: SK U/2,8 P2,54 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SK U/2,8 P2,54 WH CUS
Catalog number	0825136
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-E04F7F20DC
Generated	2026-08-05

Product Overview

Marker strip

Marking strip, Elbow, available: Elbow, white, labelled according to customer specifications, mounting class: glued, for terminal width: 2.54 mm, usable area: 186 x 2.8 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0825136

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4046356354875

Weight per Piece (excluding packing) 9.000 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 186 mm

Width (a) 2.8 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C

Ambient temperature (assembly) > 0 °C

Recommended storage conditions 20-25 °C / 40-50 % relative humidity.

General

Color white

Type adhesive

Components free from silicone and halogen

Material Polyester

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of marker strips 50

Adhesive Acrylic

Printability Office printing systems

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Foil strength 50 µm

Adhesive strength 20 µm

Marking mounting type adhesive

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Environmental Product Compliance

China RoHS For details about hazardous substances go to ta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SK U/2,8 P2,54 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.