

INDUSTRIAL COMPONENT DATA

HC-STA-B24-HLFS-1TTM32-EL-AL 1412789 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-STA-B24-HLFS-1TTM32-EL-AL



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-STA-B24-HLFS-1TTM32-EL-AL
Catalog number	1412789
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-4E12F6CC9D
Generated	2026-08-05

Product Overview

Housing

B24 aerial housing, for longitudinal flange, material: Die-cast aluminum, seawater resistant, cable outlets: 1, straight, 1x M32, height: 60 mm, cable gland: without, Standard

B24 protective housing, for longitudinal locking, material: Die-cast aluminium, waterproof, cable outlets: 1, straight, 1x M32, height: 60 mm, screw connection for cable: without, Standard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1412789

Packing unit 1 pc

Catalog page Page 624 (C-2-2017)

GTIN 4055626060552

Weight per Piece (excluding packing) 240.800 g

Custom tariff number 85389099

Country of origin PL (Poland)

Dimensions

Height 60 mm

Width 44 mm

Length 120 mm
Ambient conditions
Degree of protection (IP) IP66
IP67
Degree of protection (NEMA) 4 (UL 50e)
4X (UL 50e)
12 (UL 50e)
Ambient temperature (operation) -40 °C ... 125 °C
General
Note for contact inserts HC-B24, BB46, D64, DD108, HV10/16, M
Size B24
Housing type Sleeve housing
Color gray aluminum
Locking type for single locking latch
No. of cable outlets 1
Cable outlet straight
Screw connection none
Type of the screw connection 1x M32
Housing material Die-cast aluminum, salt water resistant
Housing surface material uncoated
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202
ETIM 5.0EC000437ETIM 6.0EC000437
UNSPSC 13.231261501
ETIM for 1412789 Connectors (EC000437)
Feature Name
Feature Value
Width (EF000008)
44 mm
Height (EF000040)
60 mm
Depth (EF000049)
120 mm
Type of housing (EF006980)
Plug case
Housing material (EF001596)
Aluminium
Coating housing (EF001601)
Uncoated
Housing colour (EF000136)
Other
Position cable feed (EF008218)
Other
Position of the shackle (EF008459)

None

With c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-STA-B24-HLFS-1TTM32-EL-AL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.