

INDUSTRIAL COMPONENT DATA

HC-HPR-B06-HHWH-1TTM25-EM-BK 1411106 PHOENIX CONTACT Housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-HPR-B06-HHWH-1TTM25-EM-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-HPR-B06-HHWH-1TTM25-EM-BK
Catalog number	1411106
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-326CB452EB
Generated	2026-08-05

Product Overview

Housing

B6 aerial housing, with screw lock, material: Die-cast aluminum, cable outlets: 1, straight, 1x M25, height: 100.5 mm, cable gland: without, protective cap: no, Railway applications, for high EMC and environmental requirements, HPR Series B6 protective housing, with screw locking, material: Die-cast aluminium, cable outlets: 1, straight, 1x M25, height: 100.5 mm, screw connection for cable: without, protective cover: no, Railway applications, for high environmental and EMC requirements, HPR series

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1411106

Packing unit 1 pc

Catalog page Page 626 (C-4-2015)

GTIN 4046356921404

Weight per Piece (excluding packing) 490.000 g

Custom tariff number 85389099

Country of origin CN (China)

Dimensions

Height 100.5 mm

Width 58 mm

Length 132 mm

Ambient conditions

Degree of protection of housing (IP) IP66

IP68 (0.5 bar / 24 h)

IP69K (ISO 20653:2013-02)

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B6, BB10, DD24, M Tall housings for extra large wiring space

Size B6

Housing type Sleeve housing

Color black

Locking type with screw locking

No. of cable outlets 1

Cable outlet straight

Screw connection none

Type of the screw connection 1x M25

Protective cover no

Housing material Aluminum die-cast

Housing surface material Powder-coated, black

Seal material NBR

Cable gland material Stainless steel

Material of locking screw Stainless steel

Assembly instructions M6 locking screw, slotted hexagon head screw (SW10), tightening torque: 4 Nm

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss 7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 13.231261501

ETIM for 1411106 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

58 mm

Height (EF000040)

100.5 mm

Depth (EF000049)

132...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-HPR-B06-HHWH-1TTM25-EM-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.