

INDUSTRIAL COMPONENT DATA

HC-B 10-TFQ-H-O1STM25G 1460080 PHOENIX CONTACT HEAVYCON sleeve housing B10, for double locking latch, height..

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 10-TFQ-H-O1STM25G



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 10-TFQ-H-O1STM25G
Catalog number	1460080
Category	Housing for rectangular connectors
Minimum order	10 Pcs
Document ID	EO-14E020767C
Generated	2026-08-03

Product Overview

HEAVYCON sleeve housing B10, for double locking latch, height 72 mm, with thread 1x M25, straight conductor exit
HEAVYCON B10 aerial housing, for cross flange, height 72 mm, with 1x M25 thread, straight cable outlet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Dimensions

Height 72 mm

Width 43 mm

Length 73 mm

Ambient conditions

Degree of protection of housing (IP) IP65

Ambient temperature (operation) -40 °C ... 125 °C

General

Note For contact inserts HC-B10, BB18, DD42, M, K8/24

Type B10

Housing type Sleeve housing

Locking type For double locking latch

No. of cable outlets 1

Cable exit straight

Screw connection none

Type of the screw connection 1x M25

Housing material Aluminum die-cast

Housing surface material Powder-coated, gray

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 10-TFQ-H-O1STM25G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.