

INDUSTRIAL COMPONENT DATA

VC-K-T2-IN (10-25) G 1583880 PHOENIX CONTACT Sleeve housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: VC-K-T2-IN (10-25) G



Manufacturer	PHOENIX CONTACT
MPN / Reference	VC-K-T2-IN (10-25) G
Catalog number	1583880
Category	Housing for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-F2B42501D7
Generated	2026-08-03

Product Overview

Sleeve housing

Aerial housing, Product family: VARIOCON, construction: VC2, housing material: Polyamide, color: black, minimum cable diameter: 10 mm, maximum cable diameter: 25 mm. In the use of fibre optic conductors, the bending radii of the cable manufacturer must be considered.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1583880

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 35 (C-2-2013)

GTIN 4046356569620

Weight per Piece (excluding packing) 105.100 g

Custom tariff number 85389099

Country of origin DE (Germany)

Dimensions

Height 81 mm

Ambient conditions

Degree of protection IP65

Ambient temperature (operation) -40 °C ... 80 °C

General

Note When using fiber optics, the bending radii of the cable manufacturers must be observed.

Type VC2

Degree of protection IP65

Flammability rating according to UL 94 V0

Locking type Screw locking, Allen screw

Fixing screws M4 (3 mm Allen screw)

Tightening torque, mounting screw 1.5 Nm $\pm$ 0.3 Nm

Type of the screw connection Pg29

Cable outlet straight

Housing material Polyamide

Seal material NBR

Ambient temperature (operation) -40 °C ... 80 °C

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027140816eCl@ss 4.127140816eCl@ss 5.027371205eCl@ss 5.127261200eCl@ss 6.027261200eCl@ss

7.027440202eCl@ss 8.027440202eCl@ss 9.027440202

ETIM 4.0EC000437ETIM 5.0EC000437ETIM 6.0EC000437

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC

13.231261501

ETIM for 1583880 Connectors (EC000437)

Feature Name

Feature Value

Width (EF000008)

38 mm

Height (EF000040)

86 mm

Depth (EF000049)

78 mm

Coating housing (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VC-K-T2-IN (10-25) G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.