

INDUSTRIAL COMPONENT DATA

UGSK/S + GS 0313085 PHOENIX CONTACT Slide-type terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UGSK/S + GS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UGSK/S + GS
Catalog number	0313085
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-DD8C2A80D0
Generated	2026-08-01

Product Overview

Slide-type terminal block

Sliding link terminal, with sliding link, nominal voltage: 500 V, nominal current: 41 A, number of connections: 2, connection type: Screw connection, 1st floor, Dimensioning section: 6 mm², cross-section: 0.5 mm² - 10 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 0313085

Packing unit 50 pc

Catalog page Page 481 (C-1-2017)

GTIN 4017918001681

Weight per Piece (excluding packing) 31.380 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 6 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 41 A
Maximum load current 57 A (with 10 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Dimensions
Length 61 mm
Width 8.2 mm
Height NS 35/7,5 52.7 mm
Height NS 35/15 60.2 mm
Height NS 32 57.6 mm
Connection data
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 8
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
2 conductors with same cross section, solid min. 0.5 mm²
2 conductors with same cross section, solid ma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UGSK/S + GS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.