

INDUSTRIAL COMPONENT DATA

SLK 16-EX 0523998 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SLK 16-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SLK 16-EX
Catalog number	0523998
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-FF73F953BE
Generated	2026-08-04

Product Overview

Ground modular terminal block

Ground terminal block for rail, connection type: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 16 mm², AWG: 20 - 6, width: 10 mm, color: silver, mounting class: NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 0523998

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918002725

Weight per Piece (excluding packing) 25.030 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 10 mm²

Color silver

Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.82 W
Maximum load current 76 A (for 16 mm² conductor cross section)
Open side panel No
Dimensions
Width 10 mm
Length 26 mm
Height NS 32 44 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 10 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 8
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 6 mm²
2 conductors with same cross section, solid min. 0.5 mm²
2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SLK 16-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.