

INDUSTRIAL COMPONENT DATA

SLK 4-EX 0521990 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SLK 4-EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	SLK 4-EX
Catalog number	0521990
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-C311C1BA92
Generated	2026-08-04

Product Overview

Ground modular terminal block

Ground terminal for rail, connection type: Screw connection, number of connections: 2, cross-section: 0.2 mm² - 4 mm², AWG: 24 - 12, width: 7 mm, color: silver, mounting class: NS 32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0521990

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918002701

Weight per Piece (excluding packing) 13.410 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color silver

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Open side panel No

Dimensions

Width 7 mm

Length 27 mm

Height NS 32 33 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1 mm²

2 conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SLK 4-EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.