

INDUSTRIAL COMPONENT DATA

SM-5ES1N8AYW00S 1613525 PHOENIX CONTACT Device connector, front mounting with knurled nut

Brand: PHOENIX CONTACT | Manufacturer Part Number: SM-5ES1N8AYW00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SM-5ES1N8AYW00S
Catalog number	1613525
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-8613390BFF
Generated	2026-08-05

Product Overview

Device connector, front mounting with knurled nut

Plug-in connector for front wall appliances with knurled nut, angled, fixed, SPEEDCON lock, M40, number of poles: 2+3+PE, contact type: Female, Axial O-ring, 4x Ø4.2, shielded: yes, flange measurement: 40 mm x 40 mm, protection index: IP67, connection type: Crimped connection, series: SM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1613525

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 167 (C-2-2017)

GTIN 4046356400831

Weight per Piece (excluding packing) 532.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts 2 x Ø 2 mm, 4 x Ø 3.6 mm separately

Type of locking SPEEDCON locking

Coding N

Contact connection method Crimp connection

Type of contacts Socket

Contact diameter of power contacts 3.6 mm

Nominal current per power contact at 25°C 70 A

Contact diameter of signal contacts 2 mm

Nominal current per signal contact at 25°C 30 A

Pg housing screw connection none

Mounting type 4x Ø4,2

Ambient conditions

Ambient temperature -40 °C ... 125 °C

Degree of protection IP67

Material

Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Insulator material PA 6.6

Gasket and O-ring material FPM

Specifications according to DIN EN 61984:2001

Installation height max. 3000 m

Nominal / operating voltage of power contacts 630 V

Rated surge voltage of power contacts 6 kV

Overvoltage category of power contacts III

Degree of pollution of power contacts 3

Nominal / operating voltage of signal contacts 250 V

Rated surge voltage of signal contacts 4 kV

Overvoltage category of signal contacts III

Degree of pollution of signal contacts 3

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous subst...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SM-5ES1N8AYW00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.