

INDUSTRIAL COMPONENT DATA

SM-7EP1N8AC004 1605832 PHOENIX CONTACT Rear panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SM-7EP1N8AC004



Manufacturer	PHOENIX CONTACT
MPN / Reference	SM-7EP1N8AC004
Catalog number	1605832
Category	Sensor-actuator connector chassis
Minimum order	6 Pcs
Document ID	EO-E4E7F1D7C2
Generated	2026-08-06

Product Overview

Rear panel feed-through

Rear wall pass-through, Short straight, Screw lock, M40, number of poles: 4+3+PE, contact type: Pin, Axial O-ring, 4xM4, shielded: yes, cable diameter range: 17 mm ... 21 mm, number of poles: 8, connection type: Crimped connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1605832

Packing unit 6 pc

Note Made to Order (non-returnable)

GTIN 4046356255165

Weight per Piece (excluding packing) 515.630 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Note Order information: Order crimp contacts 4 x Ø 2 mm, 4 x Ø 3.6 mm separately

Type of locking Screw locking

Coding N

Contact connection method Crimp connection

Type of contacts Pin
Number of positions 8
Contact diameter of power contacts 3.6 mm
Nominal current per power contact at 25°C 70 A
Contact diameter of signal contacts 2 mm
Nominal current per signal contact at 25°C 30 A
Conductor entry 17 mm ... 21 mm
Pg housing screw connection none
Mounting type 4xM4
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 250 V
Rated surge voltage of signal contacts 4 kV
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about haz...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SM-7EP1N8AC004 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.