

INDUSTRIAL COMPONENT DATA

SMKDS 2,5/16-5,08GYBD:151-44 1092962 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 20..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 2,5/16-5,08GYBD:151-44



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 2,5/16-5,08GYBD:151-44
Catalog number	1092962
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-9E725B090C
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, nominal current: 20 A, pitch: 5,08 mm, number of poles: 16, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 50 °, color: grey

Terminal block for printed circuit board, nominal current: 20 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 2.5 mm², Number of rows: 1, Number of poles per row: 16, article family: SMKDS 2.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor connection direction/printed circuit board: 50 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 2,5/16-5,08GYBD:151-44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.