

INDUSTRIAL COMPONENT DATA

SMKDS 2,5/ 8-5,08 GY35BDL1-L3 1153393 PHOENIX CONTACT Printed circuit board terminal, rated current: 20 A, S..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 2,5/ 8-5,08 GY35BDL1-L3



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 2,5/ 8-5,08 GY35BDL1-L3
Catalog number	1153393
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-D724676D1A
Generated	2026-08-05

Product Overview

Printed circuit board terminal, rated current: 20 A, sizing voltage (III/2): 400 V, nominal section: 2.5 mm², Number of rows: 1, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave welding, connection direction conductor/printed circuit board: 50 °, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 2,5/ 8-5,08 GY35BDL1-L3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.