

INDUSTRIAL COMPONENT DATA

SMKDS 3/ 11 GY 1016031 PHOENIX CONTACT Terminal for printed circuit board, rated voltage: 400 V, pitch: 5 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 3/ 11 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 3/ 11 GY
Catalog number	1016031
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-C6A449DBF4
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, rated voltage: 400 V, pitch: 5 mm, number of poles: 11, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: gray

Terminal block for printed circuit board, rated current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 11, Number of rows: 1, Number of poles per row: 11, article family: SMKDS 3, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Conductor connection direction/printed circuit board: 55 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.5mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 3/ 11 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.