

INDUSTRIAL COMPONENT DATA

SMKDS 3/ 6-5,08 BD:NC,11-15 1743281 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 24 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDS 3/ 6-5,08 BD:NC,11-15



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDS 3/ 6-5,08 BD:NC,11-15
Catalog number	1743281
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-FB9FBB3F19
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, nominal current: 24 A, pitch: 5,08 mm, number of poles: 6, type of connection: Connection by screw with capsule-traction, assembly: Soldering by wave direction for connection conductor/pcb: 55 °, color: green
Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 6, Number of rows: 1, Number of poles per row: 6, family of articles: SMKDS 3, pitch: 5.08mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Connection direction driver/printed circuit board: 55 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 4.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDS 3/ 6-5,08 BD:NC,11-15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.