

## INDUSTRIAL COMPONENT DATA

# SMKDSN 1,5/ 8-5,08 BDWH:5-8 1701732 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSN 1,5/ 8-5,08 BDWH:5-8



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SMKDSN 1,5/ 8-5,08 BDWH:5-8    |
| Catalog number  | 1701732                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 50 Pcs                         |
| Document ID     | EO-9AAC17F299                  |
| Generated       | 2026-08-06                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, dimensioning voltage (III/2): 400 V, nominal section: 1.5 mm<sup>2</sup>, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, article family: SMKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, mounting: Wave soldering, Driver/PCB connection direction: 45°, Color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, Packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1701732

Packing unit 1

GTIN 4046356557702

Custom tariff number 85369010

Dimensions

Length [ l ] 12 mm

Pitch 5.08 mm

Dimension a 35.56 mm

Width [ w ] 41.64 mm

Height 11 mm

Height [ h ] 14.5 mm

Solder pin [P] 3.5 mm

Hole diameter 1.3 mm

#### General

Range of articles SMKDSN 1,5

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 13.5 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 13.5 A

Insulating material PA

Solder pin surface

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 6 mm

Number of positions 8

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

#### Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

2 conductors with same cross section, solid min. 0.14 mm<sup>2</sup>

2 conductors with same cross section, solid max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.14 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 0.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm<sup>2</sup>

2 conductors with same...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSN 1,5/ 8-5,08 BDWH:5-8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.