

INDUSTRIAL COMPONENT DATA

SMKDSP 1,5/18 1064320 PHOENIX CONTACT Terminal for printed circuit board, pitch: 5 mm, number of poles: 18, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSP 1,5/18



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDSP 1,5/18
Catalog number	1064320
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-2FB1381D0C
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, pitch: 5 mm, number of poles: 18, type of connection: Connection by screw with capsule-traction, assembly: wave Soldering, color: green

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm², number of rows: 1, number of poles per row: 18, family of articles: SMKDSP 1.5, pitch: 5 mm, type of connection: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/printed circuit board connection direction: 55°, color: green, Pin length [P]: 3.5 mm, number of soldering pins per potential: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1064320 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

18.8 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

17.5 A
Rated voltage (EF000228)
400 V
Rated surge voltage (EF002993)
4 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2
Connection type conductor (EF006821)
Screw connection
Connectable conductor cross section solid-core (EF007337)
0.14 mm²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)
0.25 mm²
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)
0.14 mm²
Connectable conductor cross section multi-wired (EF007343)
0.14 mm²
Connection type PCB (EF006822)
Soldering connection
Material connection surface (EF006826)
Tin
Diameter connection pin (EF006823)
1.3 mm
Length pin (EF006825)
3.5 mm
Material insulation body (EF007543)
Other
Housing colour (EF000136)
Green
Inflammability class of insulation material according to UL94 (EF002521)
V0
Operating temperature (EF002393)
-40 °C
Type of PCB fastening (EF008226)
Connecting contact
Type of fastening (EF002442)
Solder
Type of banding (EF007011)
Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSP 1,5/18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.