


INDUSTRIAL COMPONENT DATA

**SMKDSP 1,5/ 3-5,08 BD:+W- 1053333 PHOENIX CONTACT
PCB terminal block, nominal current: 17.5 A, rated voltage..**

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSP 1,5/ 3-5,08 BD:+W-



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDSP 1,5/ 3-5,08 BD:+W-
Catalog number	1053333
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-941E5C5EEF
Generated	2026-08-04

Product Overview

PCB terminal block, nominal current: 17.5 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm², pitch: 5.08 mm, number of positions: 3, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 55 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm², number of rows: 1, number of poles per row: 3, article family: SMKDSP 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 55°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data
Orderkey 1053333
Packing unit 1
GTIN 4055626678924
Custom tariff number 85369010
Item properties
Connection capacity
Material data - housing

Dimensions for PCB design

General product information

Air clearances and creepage distances

Classifications

Electrical parameters

Material data - contact

Dimensions for the product

Packaging information

Electrical tests

Environmental Product Compliance

Item properties

Brief article description PCB terminal block

Range of articles SMKDSP 1,5

Pitch 5.08 mm

Number of positions 3

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 1

Back to topElectrical parameters

Nom. voltage 400 V

Back to topConnection capacity

Connection method Screw connection with tension sleeve

pluggable no

Conductor cross section solid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 26 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.5 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSP 1,5/ 3-5,08 BD:+W- with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.