

INDUSTRIAL COMPONENT DATA

SMKDSP 1,5/ 4-5,08 BD:21-2BSO 1258178 PHOENIX CONTACT

Terminal block for printed circuit board, nominal curr..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSP 1,5/ 4-5,08 BD:21-2BSO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDSP 1,5/ 4-5,08 BD:21-2BSO
Catalog number	1258178
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-B9A973371E
Generated	2026-08-05

Product Overview

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 400 V, nominal section: 1.5 mm², number of rows: 1, number of poles per row: 4, family of articles: SMKDSP 1.5, pitch: 5.08 mm, type of connection: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, Mounting: Wave soldering, conductor/PCB connection direction: 55°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, number of solder pins per potential: 1, packaging type: boxed

Printed circuit board terminal, rated current: 17.5 A, sizing voltage (III/2): 400 V, nominal section: 1.5 mm², Number of rows: 1, Number of poles per row: 4, item family: SMKDSP 1.5, pitch: 5.08 mm, connection type:Screw connection with traction capsule, mounting: Wave welding, connection direction conductor/printed circuit board: 55 °, color: green, Pin length [P]: 3.5 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1258178 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

18.8 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5.08 mm

Rated current I_n (EF008250)

17.5 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.14 mm²

Connectable conductor cross section multi-wired (EF007343)

0.14 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSP 1,5/ 4-5,08 BD:21-2BSO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.