


INDUSTRIAL COMPONENT DATA

SMKDSP 1,5/ 4 GY BD:1-4Q 1111592 PHOENIX CONTACT PCB terminal block, pitch: 5 mm, number of positions: 4, co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMKDSP 1,5/ 4 GY BD:1-4Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMKDSP 1,5/ 4 GY BD:1-4Q
Catalog number	1111592
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-84A50AB4B2
Generated	2026-08-06

Product Overview

PCB terminal block, pitch: 5 mm, number of positions: 4, color: gray, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm
Printed circuit board terminal, rated current: 17.5 A, sizing voltage (III/2): 400 V, nominal section: 1.5 mm², Number of rows: 1, Number of poles per row: 4, item family: SMKDSP 1.5, pitch: 5 mm, connection type: Screw connection with traction capsule, mounting: Wave welding, connection direction conductor/printed circuit board: 55°, color: grey, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, packaging type:boxed packaging

Printed circuit board terminal, nominal current: 17.5 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm², number of rows: 1, number of positions per row: 4, product range: SMKDSP 1,5, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, mounting: Wave soldering, conductor/PCB connection direction: 55 °, color: gray, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 1, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family SMKDSP 1,5

Product line COMBICON Terminals S

Number of positions 4

Pitch 5 mm

Number of rows 1

Pin layout Linear pinning

Solder pins per potential 1

Data management status

Article revision 01

Electrical propertiesNominal current I_N 17.5 A

Nominal voltage U_N 400 V

Rated voltage (III/3) 250 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Type PC termination block

Nominal cross section 1.5 mm²

Conductor connection

Connection method Screw connection with tension sleeve

Conductor cross section rigid 0.14 mm² ... 2.5 mm²

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section AWG 26 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 0.5 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Stripping length 7 mm

Drive form screw head Slotted (L)

Tightening torque 0.5 Nm ... 0.6 Nm

MountingMounting type Wave solder...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMKDSP 1,5/ 4 GY BD:1-4Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.