

INDUSTRIAL COMPONENT DATA

UTME 6-SET POWER 3036000 PHOENIX CONTACT Starter kit

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTME 6-SET POWER



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTME 6-SET POWER
Catalog number	3036000
Category	Installation clamp for meters
Minimum order	1 Pcs
Document ID	EO-89D2BFD8EE
Generated	2026-08-05

Product Overview

Starter kit

Beginner's kit consisting of measuring transducer disconnecter terminals in quick-connect technology, marking material, bridging and test accessories. A terminal strip can be individually mounted for three-phase transformer switching (current and voltage).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3036000

Packing unit 1 pc

GTIN 4046356416993

Weight per Piece (excluding packing) 1,000.000 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Note Quantity specifications on the set contents under downloads

Set consists of 3047400 UTME 6

3047442 UTMED 6-PE

3047426 D-UTME 6

0311139 ATP-URTK/SP

3034387 CARRIER 35-8

3034468 SB-ME 2-8

3030284 FBS 2-8

3032389 FBS 1/3/5-8

3032745 PAI-4-FIX YE

3032758 PAI-4-FIX GN

3032761 PAI-4-FIX VT

3032729 PAI-4-FIX BU

3034439 S-ME 6

3022276 CLIPFIX 35-5

0811969 KLM 3

0819327 UC-EMLP (20X8)

0818072 UC-TM 8

Dimensions

Width 225 mm

Length 315 mm

Height 65 mm

Connection data

Connection method Screw connection

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Articles in set

Test disconnect terminal block, nom. voltage: 500 V, nominal current: 30 A, connection method: Screw connection, cross section: 0.2 mm² - 10 mm², AWG: 24 - 8, length: 100.8 mm, width: 8.2 mm, color: gray, mounting: NS 35/7,5, NS 35/15, nom. voltage: 500 V

Ground modular terminal block, connection method: Screw connection, number of connections: 2, cross section: 0.2 mm² - 10 mm², AWG: 24 - 8, width: 8.2 mm, color: green-yellow, mounting type: NS 35/7,5, NS 35/15

End cover, length: 100.8 mm, width: 2.2 mm, height: 49.6 mm, color: gray

Partition plate, length: 99 mm, width: 2 mm, height: 64 mm, colo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTME 6-SET POWER with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.