

INDUSTRIAL COMPONENT DATA

MKDSN 2,5/ 4 BD:89-92 1707951 PHOENIX CONTACT Terminal block for printed circuit board, rated current: 16 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 2,5/ 4 BD:89-92



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKDSN 2,5/ 4 BD:89-92
Catalog number	1707951
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-D26C1CD796
Generated	2026-08-06

Product Overview

Terminal block for printed circuit board, rated current: 16 A, rated voltage: 400 V, pitch: 5 mm, number of poles: 4, connection type: Screw connection with traction capsule, mounting: Wave soldering, connection direction driver/printed circuit board: 0 °, color: green

Terminal block for printed circuit board, nominal current: 24 A, dimensioning voltage (III/2): 400 V, nominal section: 2.5 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, family of articles: MKDSN 2.5, pitch: 5 mm, type of connection: Screw connection with traction capsule, mounting: Wave soldering, Connection direction driver/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 16 A, nom. voltage: 400 V, pitch: 5 mm, number of positions: 4, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green
Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsExtremely small design for the respective conductor cross sectionIntegrated protective guide prevents incorrect insertion of the conductor underneath the tension sleeveThe latching on the side enables various numbers of positions to be combinedKey Commercial Data

Orderkey 1707951

Packing unit 1

GTIN 4046356954457

Custom tariff number 85369010

Electrical parameters

Rated current 16 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 0.75 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²

Stripping length 6.5 mm

Material data - conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 2,5/ 4 BD:89-92 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.