

INDUSTRIAL COMPONENT DATA

SMSTB 2,5/ 7-ST BD:1-7 1712702 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTB 2,5/ 7-ST BD:1-7



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMSTB 2,5/ 7-ST BD:1-7
Catalog number	1712702
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-12527556FC
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, family of articles: SMSTB 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, conductor connection direction/printed circuit board: -45 °, Stecksystem: CLASSIC COMBICON, Lock: without, packaging type: boxed

Printed circuit board connector, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: SMSTB 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: -45 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1712702

Packing unit 1

GTIN 4055626311852

Custom tariff number 85366990

Dimensions

Height [h] 15.5 mm

Pitch 5 mm

Dimension a 5 mm

General

Range of articles SMSTB 2,5/...-ST

Number of positions 7

Connection method Screw connection with tension sleeve

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread M3

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTB 2,5/ 7-ST BD:1-7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.