

INDUSTRIAL COMPONENT DATA

SMSTB 2,5/ 8-ST-5,08 AU 1003540 PHOENIX CONTACT

Connector for printed circuit board, number of poles: 8, pit..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTB 2,5/ 8-ST-5,08 AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMSTB 2,5/ 8-ST-5,08 AU
Catalog number	1003540
Category	Cable connector
Minimum order	500 Pcs
Document ID	EO-3CE79DC697
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 8, pitch: 5,08 mm, type of connection: Connection by screw with capsule-wheel drive, color: green, surface, contacts: Gold

Connector for printed circuit board, nominal section: 2.5 mm², color: green, rated current: 12 A, sizing voltage (III/2): 320 V, surface contacts: Gold, contact type: Connection female, Number of potentials: 8, Number of rows: 1, Number of poles per row: 8, number of connections: 8, article family: SMSTB 2.5/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: -45 °, Stecksystem: CLASSIC COMBICON, Lock: without, type of packaging: boxed packaging

PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Gold, contact connection type: Socket, number of potentials: 8, number of rows: 1, number of positions: 8, number of connections: 8, product range: SMSTB 2,5/..-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: -45 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors M

Product type PCB connector

Product family SMSTB 2,5/..-ST

Number of positions 8

Pitch 5.08 mm
Number of connections 8
Number of rows 1
Number of potentials 8
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 320 V
Degree of pollution 3
Contact resistance 2.3 mΩ
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MSTB 2,5
Nominal cross section 2.5 mm²
Contact connection type Socket
Interlock
Locking type without
Mounting flange without
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction -45 °
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with same cross section, solid 0.2 mm² ... 1 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTB 2,5/ 8-ST-5,08 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.