

INDUSTRIAL COMPONENT DATA

SMSTBA 2,5/ 2-G-5,08 BK 1801108 PHOENIX CONTACT PCB headers, nominal current: 12 A, rated voltage (III/2): 3..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTBA 2,5/ 2-G-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SMSTBA 2,5/ 2-G-5,08 BK
Catalog number	1801108
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3FA992CC66
Generated	2026-08-02

Product Overview

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 2, pitch: 5.08 mm, color: black, contact surface: Tin, mounting: Wave soldering

Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: SMSTBA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 2, pitch: 5.08 mm, color: black, contact surface: Tin, mounting: Wave soldering

Key Commercial Data

Orderkey 1801108

Packing unit 1

GTIN 4055626336282

Custom tariff number 85366930

Dimensions

Length [L] 16.5 mm

Pitch 5.08 mm

Dimension a 5.08 mm

Height 15 mm

Length of the solder pin 3.5 mm

Pin dimensions 1 x 1 mm

Length 16.5 mm

General

Range of articles SMSTBA 2,5/...-G

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current IN 12 A

Flammability rating according to UL 94 V0

Color black

Number of positions 2

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCI@ss

eCI@ss 5.1 27260700

eCI@ss 6.0 27260700

eCI@ss 7.0 27440402

eCI@ss 8.0 27440402

eCI@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

ETIM for 1801108 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

2

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Rated current In (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTBA 2,5/ 2-G-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.