


INDUSTRIAL COMPONENT DATA

UCT-PMP (90X38) BU CUS 8190566 PHOENIX CONTACT

Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-PMP (90X38) BU CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-PMP (90X38) BU CUS
Catalog number	8190566
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-A5B0EF6BB7
Generated	2026-08-03

Product Overview

Snap-in markers

Snap-in sign, blue, labelled according to customer specifications, mounting type: snap onto signage stand, usable surface: 90 x 38mm, Number of individual indexes: 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > CABINET add-on**

Additional Product Information

Key Commercial Data

Orderkey 8190566

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 287 (NTK-2014)

GTIN 4046356933513

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 38 mm

Width (a) 90 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

General

Color blue

Components free from silicone and halogen

Flammability rating according to UL 94 V0

Material PVC/PC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 1

Number of individual labels per row 1

Printability Direct laser marking

Device 0831831 TOPMARK LASER

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type snapped into marker carrier

Result Test passed

Oxygen index (DIN EN ISO 4589-2) 32.4 %

R22 HL 1 - HL 3

R23 HL 1 - HL 3

R24 HL 1 - HL 3

Standards and Regulations

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Flamma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-PMP (90X38) BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.