

INDUSTRIAL COMPONENT DATA

UCT-EM (20X7) TQ CUS 0801581 PHOENIX CONTACT Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-EM (20X7) TQ CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-EM (20X7) TQ CUS
Catalog number	0801581
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-801F9C7156
Generated	2026-08-05

Product Overview

Snap-in markers

Fitting label, available: by mats, turquoise color, labeled according to customer specifications, mounting class: fit on signage support, useful surface: 20 x 7 mm, Number of individual indexes: 24

Snap-in markers, can be ordered: by sheet, turquoise, labeled according to customer specifications, mounting type: snapped into marker carrier, Number of individual labels: 24

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Labeled device marker

Data management status

Article revision 01

Marking

Number of individual labels 24

Number of individual labels per row 6

Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish

Result Test passed

UV resistance

Specification ISO 4892-2:2013-03 (following)

Result Test passed

Test duration 96 h
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Mounting Mounting type snapped into marker carrier
Material specifications RoHS compliant yes
Color turquoise green (RAL 5018)
Material PC
Flammability rating according to UL 94 V0
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components free from silicone and halogen
Environmental and real-life conditions Test for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Dimensions Width 20 mm
Length 7 mm
Standards and regulations Wipe resistance DIN EN 61010-1 (VDE 0411-1)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-EM (20X7) TQ CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.