

INDUSTRIAL COMPONENT DATA

US-EMP (35X15) SR CUS 0830355 PHOENIX CONTACT

Snap-in markers

Brand: PHOENIX CONTACT | Manufacturer Part Number: US-EMP (35X15) SR CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	US-EMP (35X15) SR CUS
Catalog number	0830355
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-B399847132
Generated	2026-08-03

Product Overview

Snap-in markers

Sign to fit, available: by card, silver, labeled according to customer's instructions, mounting class: fit in support for signage, useful surface: 35 x 15 mm, Number of individual indexes: 24

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0830355

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 265 (C-5-2013)

GTIN 4046356715898

Weight per Piece (excluding packing) 14.860 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 15 mm

Width (a) 35 mm

Height (c) 0.5 mm

Ambient conditions

Ambient temperature (operation) -30 °C ... 80 °C

Recommended storage conditions 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended.

General

Color silver

Components Silicone-free

Flammability rating according to UL 94 V0

Material PVC

RoHS compliant Yes

Wipe resistance DIN EN 61010-1 (VDE 0411-1)

Number of individual labels 24

Number of individual labels per row 3

Printability Thermal transfer

Device 5146464 THERMOMARK CARD

5146451 THERMOMARK CARD-US-MAG1

Ink ribbon 0801371 THERMOMARK-RIBBON 110-TC

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification following DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions IEC 61010-1:2010-06

Result Test passed

Foil strength 500 µm

Marking moun...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-EMP (35X15) SR CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.