

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSD-4CON-SH TOR 32 1457636 PHOENIX CONTACT Bus system flat-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSD-4CON-SH TOR 32



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSD-4CON-SH TOR 32
Catalog number	1457636
Category	Contact insert for circular connectors
Minimum order	100 Pcs
Document ID	EO-0FB935D88F
Generated	2026-07-31

Product Overview

Bus system flat-type plug

Plug-in Mounting Connector, 4-Pole, Female Connection, Straight, M12, Coding: D, Printed Circuit Board Mounting, Solder Connection THR, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) Item code: 1237400

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1457636

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

Catalog page Page 257 (C-2-2013)

GTIN 4046356617383

Weight per Piece (excluding packing) 6.860 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection correctly plugged in and locked

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D - data

Standards/regulations M12 connector IEC 61076-2-101

Overvoltage category II

Degree of pollution 3

Connection method THR solder connection

Insertion/withdrawal cycles > 100

Mounting type PCB mounting

Type of packaging Belt

Delivery state with assembly pad

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSD-4CON-SH TOR 32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.