

INDUSTRIAL COMPONENT DATA

SACC-DSI-M5FS-4CON-L180 1530650 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M5FS-4CON-L180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M5FS-4CON-L180
Catalog number	1530650
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-46124B661D
Generated	2026-07-29

Product Overview

Flush-type connector

Sensor/actuator mounting female, 4-pole, M5, backwall mount/bolt-on mount, with straight weld connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1530650

Packing unit 20 pc

Note Made to Order (non-returnable)

Catalog page Page 224 (C-2-2013)

GTIN 4046356024457

Weight per Piece (excluding packing) 4.270 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C

Degree of protection IP67

General

Rated current at 40°C 1 A

Rated voltage 60 V
Number of positions 4
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M5 connector IEC 61076-2-105
Status display No
Overvoltage category II
Degree of pollution 3
Test voltage 800 V
Connection method Solder pins
Mounting type Rear mounting M5 x 0.5 With locking nut
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Au
Contact carrier material PA 6.6
Material, knurls Nickel-plated brass
Sealing material Viton
Cable
Standards/specifications M5 connector IEC 61076-2-105
Standards and Regulations
Standard designation M5 connector
Standards/regulations IEC 61076-2-105
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 25;
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 2.0EC001297ETIM 3.0EC002061ETIM 4.0EC002...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M5FS-4CON-L180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.