

INDUSTRIAL COMPONENT DATA

SACC-DSIV-FS-8CON-L180-10G SCO 1440669 PHOENIX CONTACT Flush-type socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSIV-FS-8CON-L180-10G SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSIV-FS-8CON-L180-10G SCO
Catalog number	1440669
Category	Circular connector, mounting (PCB)
Minimum order	20 Pcs
Document ID	EO-CF5D152871
Generated	2026-08-01

Product Overview

Flush-type socket

Conect. plug. to be apar. poster wall, 8-pole, Female connection, straight, M12-SPEEDCON, coding: X, Rear mounting, THR weld connection, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) art.code: 1237426

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1440669

Packing unit 20 pc

Minimum order quantity 20 pc

Note Made to Order (non-returnable)

Catalog page Page 90 (C-2-2013)

GTIN 4046356504591

Weight per Piece (excluding packing) 10.530 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Degree of protection IP67 (When plugged in)

General

Rated current at 40°C 0.5 A

Rated voltage 50 V AC

60 V DC

Rated surge voltage 1.5 kV

Number of positions 8

Insulation resistance > 100 MΩ

Signal type/category Ethernet CAT6A

Overvoltage category III

Degree of pollution 3

Connection method THR solder connection

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PPA

Material of grip body Zinc die-cast, nickel-plated

Material, knurls Zinc die-cast, nickel-plated

Material Zinc die-cast (nickel-plated)

Sealing material EPDM

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

ClassificationseCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 2.0EC001297ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / SACC-DSIV-FS-8CON-L180-10G SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.