

INDUSTRIAL COMPONENT DATA

SACC-DSIV-FSB-5CON-L180 SCOTHR 1542635 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSIV-FSB-5CON-L180 SCOTHR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSIV-FSB-5CON-L180 SCOTHR
Catalog number	1542635
Category	Circular connector, mounting (PCB)
Minimum order	60 Pcs
Document ID	EO-2B26D09B09
Generated	2026-08-02

Product Overview

Panel feed-through

Conect. plug. to be apar. wall poster., 5-pole, Female connection, straight, M12-SPEEDCON, coding: B, Rear mounting, M12 x 1, Weld connection THR, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1239955

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1542635

Packing unit 60 pc

Minimum order quantity 60 pc

Note Made to Order (non-returnable)

Catalog page Page 189 (C-2-2013)

GTIN 4046356097901

Weight per Piece (excluding packing) 10.290 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding B - inverse

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method THR solder connection

Mounting type Rear mounting M12 x 1 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PPA

Material, knurls Zinc die-cast, nickel-plated

Sealing material FKM / EPDM

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSIV-FSB-5CON-L180 SCOTHR with the required quantity to info@electricaonline.com
or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.